

TAGELUS® TAGELUS® II WITH CLEARPRO TECHNOLOGY®



Tagelus® II

Tagelus®

A TIME-PROVEN TECHNOLOGY ...

Sand filters have been installed on millions of pools for decades. But not all sand filters are equal, because not all include design features that continuously level the sand inside the tank. This is the key to consistent performance and quicker cleaning cycles. It is also a key advantage when you select a Tagelus fiberglass sand filter.

Features:

- Constructed in one piece from fiberglassreinforced material to deliver unmatched strength and durability for years of service.
- A special "diffuser" creates a uniform sand bed that consistently traps more dirt without impeding the water flow—the result is more effective filtration and longer times between backwashing.
- Tagelus filters provide years of service with only periodic backwashing to remove trapped debris from the sand
- Top-mounted six-position multi-port valve with sight glass, built-in pressure gauge, manual air relief valve, flange connections and clamp ring to make inspection and routine maintenance fast, easy and safe.



Now even better with ClearPro

Tagelus is now also available with ClearPro Technology (Tagelus II): A patented technology to reach a very fine level of filtration, 4 times better than with a conventional sand filter. As a result the water is of crystal quality. ClearPro approaches DE filter clarity with sand filter functionality. The secret is a component inside the filter—a porous tube through which water must pass before it re-enters the pool. It creates a final barrier for the smallest particles, including the finest dust particles, algae and pollens. At the same time, Tagelus II remains the blissfully simple filter that requires less maintenance than either cartridge or diatomaceous filters. Just an occasional backwashing with the turn of a valve is all it takes to keep Tagelus II delivering the clearest water year after year.



MAXIMUM WATER CLARITY WITH MINIMAL ATTENTION

Additional features include:

- Easy-to-use water drain for simplified service and winterizing
- All internal parts are threaded for ease of maintenance
- Seamless composite construction eliminates leaks, cannot rust or corrode
- Maximum operating temperature 50°C
- 10-year limited warranty (only tank)

Model without ClearPro	Model with ClearPro	Filter Diameter (mm)	Flow Rate (m³/h)	Filter Area (m²)
F-19T6-TAG	F-19T6-TACP	480	8.5	0.17
F-24T6-TAG	F-24T6-TACP	610	7.4	0.29
F-30T8-TAG	F-30T8-TACP	762	9.8	0.45



AVAILABLE FROM:

poolemea@pentair.com www.pentairpooleurope.com

Copyright - Limited License: except as specifically permitted herein, no portion of the content on this document may be reproduced in any form or by any mean without the prior written permission of Pentair International SRL

Automation / Filters / Filter Systems / Pumps / Cleaners / White Goods / Lighting / Sanitizers / Salt Chlorinators / Dosing and Measuring Equipment / Maintenance Accessories / Water Features

